



Tragfähigkeiten Hauptausleger Lifting capacities main boom Capacités de levage flèche principale

18 t  **7,70 x 7,00 m** **360°**

Ausladung Radius		Hauptausleger · Main boom · Flèche principale									
Portée	m	10,9	16,1	21,4	25,0	31,3	37,1	42,3	46,1	50,0	
m		t	t	t	t	t	t	t	t	t	
3		80,0*									
3,5		70,0									
4		64,4	55,0								
4,5		59,3	55,0	45,0							
5		54,9	52,9	43,0	32,0						
6		51,0	49,6	41,0	32,0	17,0					
7		42,0	41,7	36,5	31,0	17,0	16,0				
8		35,0	34,8	32,0	29,0	17,0	15,5	13,0			
9		28,3	29,6	28,0	26,0	17,0	15,0	13,0	8,8		
10			25,6	24,8	23,5	17,0	14,5	12,9	8,8	7,0	
12			22,1	21,0	21,0	17,0	14,0	12,7	8,8	7,0	
14			16,1	15,8	16,8	16,1	12,7	11,8	8,8	6,9	
16				13,8	13,3	12,8	11,3	10,9	8,5	6,7	
18				11,2	10,7	10,2	10,0	10,0	8,0	6,5	
20				9,2	8,7	8,2	8,5	8,8	7,5	6,2	
22					7,2	7,0	7,4	7,3	7,0	5,9	
24						6,4	6,3	6,4	6,3	5,5	
26						5,9	5,8	5,4	5,3	5,1	
28						5,3	5,2	4,5	4,7	4,4	
30							4,5	4,0	4,0	3,7	
32								3,9	3,4	3,1	
34								3,4	3,3	2,9	
36									2,8	2,4	
38									2,4	2,0	
40									2,1	1,7	
42										1,4	
44										1,1	
46										0,8	
										0,6	

75%  **1)**

Ausladung Radius		Portée	
Portée	m	10,9	16,1
m		t	t
3			
3,5			
4		12,3	12,0
4,5		11,0	10,7
5		9,9	9,6
6		8,1	7,8
7		6,6	6,4
8		5,5	5,2
9			4,2
10			3,4
12			2,1
14			
16			
18			
20			
22			
24			
26			
28			
30			
32			
34			
36			
38			
40			
42			
44			
46			

Arbeitsbereiche Hauptausleger Working ranges main boom Portées flèche principale

